



HARDWARE SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Configuration	.19-inch rack mount, 2RU height
Dimensions (actual)	.3.44" H X 17"W X 27.8" D
Dimensions (in shipping carton)	.8.7" H X 22"W X 36" D
Weight (actual)	.41 lbs, 18.6 kg
Weight (in shipping carton)	.55 lbs, 24.9 kg
Power Supply	.110-240 VAC, 50-60 Hz, 5.0 A @ 115 VAC, 2.5 A @ 220 VAC
Rear Panel	
Traffic Ports	.2x RJ45 Gigabit Ethernet (copper) + 2x LC Gigabit Ethernet (SX fiber)
Management Port	.RJ45 Gigabit Ethernet (copper)
Serial Port	.RJ45
SVGA video port	.DB15
Front Panel	
	Power switch, power and hard drive status LEDs
Environmental Requirements (Operating)	
Temperature	.+10 C to +35 C
System Cooling Requirements	.2100 BTU/hour
Environmental Requirements (Non-operating)	
Temperature	.-40 C to +70 C
Humidity	.90% @ 28 C, non-condensing

REGULATORY CONFORMITY

Safety/EMC Class A	
Argentina	.IRAM Certificate
Canada	.UL60950 – CSA 60950 (UL and cUL)
China	.GB4943 (CNCA Certification)
Europe/CE Mark	.EN60950 (Complies with 93/68/EEC)
Germany	.S License
International	.IEC60950 (CB Report and Certificate)
Nordic Countries	.EMKO-TSE (74-SEC) 207/94
Russia	.GOST R 50377-92
United States	.UL60950 – CSA 60950 (UL and cUL)
Electromagnetic Capability - Class A	
Australia, New Zealand	.AS/NZS 3548
Canada	.ICES-003
China	.GB9254 & 17625 (CNCA Certification)
Europe/CE Mark	.EN55022, EN55024 & EN61000-3-2/-3-3 (complies with 89/336/EEC)
International	.CISPR 22
Japan	.VCCI
Korea	.RRL, MIC 1997-41 & 1997-42
Russia	.GOST R 29216-91 and 50628-95
Taiwan	.CNS13438
United States	.FCC, Part 15