



HARDWARE SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Configuration	19-inch rack mount, 1RU height
Dimensions (actual)	1.7" H X 17" W X 27.3" D
Dimensions (in shipping carton)	7.5" H X 22" W X 33.5" D
Weight (actual)	.27 lbs, 12.3 kg
Weight (in shipping carton)	.40 lbs, 18.2 kg
Power Supply	110-240 VAC, 50-60 Hz, 3.0 A @ 115 VAC, 1.5 A @ 220 VAC

Rear Panel

Management Port	RJ45 Gigabit Ethernet (copper)
Serial Port	RJ45
SVGA video port	DB15

Front Panel

Power switch, power and hard drive status LEDs

Environmental Requirements (Operating)

Temperature	+10 C to +35 C
System Cooling Requirements	1100 BTU/hour

Environmental Requirements (Non-operating)

Temperature	-40 C to +70 C
Humidity	90% @ 28 C, non-condensing

REGULATORY CONFORMITY

Safety/EMC Class A

Argentina	IRAM Certificate
Canada	UL60950 – CSA 60950 (UL and cUL)
China	GB4943 (CCC Certification)
Europe/CE Mark	EN60950 (Complies with 93/68/EEC)
Germany	S License
International	IEC60950 (CB Report and Certificate)
Nordic Countries	EMKO-TSE (74-SEC) 207/94
Russia	GOST 50377-92
United States	UL60950 – CSA 60950 (UL and cUL)

Electromagnetic Capability

Australia, New Zealand	AS/NZS 3548 (Based on CISPR 22)
Canada	ICES-003
China	GB9254 & 17625 (CCC Certification)
Europe/CE Mark	EN55022, EN55024 & EN61000-3-2/-3-3 (complies with 89/336/EEC)
International	CISPR 22
Japan	VCCI
Korea	RRL, MIC 1997-41 & 1997-42
Russia	GOST 29216-91 and 50628-95
Taiwan	CNS13438
United States	FCC, Part 15