



## HARDWARE SPECIFICATIONS

### PHYSICAL CHARACTERISTICS

|   |  |
|---|--|
| Configuration                                     | 19-inch rack mount, 1RU height                           |
| Dimensions (actual)                               | 1.7" H X 17" W X 27.3" D                                 |
| Dimensions (in shipping carton)                   | 7.5" H X 22" W X 33.5" D                                 |
| Weight (actual)                                   | .27 lbs, 12.3 kg   |
| Weight (in shipping carton)                       | .40 lbs, 18.2 kg   |
| Power Supply                                      | .110-240 VAC, 50-60 Hz, 3.0 A @ 115 VAC, 1.5 A @ 220 VAC |
| <b>Rear Panel</b>                                 |  |
| Management Port                                   | RJ45 Gigabit Ethernet (copper)                           |
| Serial Port                                       | RJ45   |
| SVGA video port                                   | DB15   |
| <b>Front Panel</b>                                |  |
| Power switch, power and hard drive status LEDs    |  |
| <b>Environmental Requirements (Operating)</b>     |  |
| Temperature                                       | +10 C to +35 C   |
| System Cooling Requirements                       | .1100 BTU/hour   |
| <b>Environmental Requirements (Non-operating)</b> |  |
| Temperature                                       | -40 C to +70 C   |
| Humidity  | .90% @ 28 C, non-condensing                              |

### REGULATORY CONFORMITY

|                                   |   |
|-----------------------------------|---|
| <b>Safety/EMC Class A</b>         |   |
| Argentina                         | IRAM Certificate  |
| Canada                            | UL60950 – CSA 60950 (UL and cUL)                                  |
| China                             | GB4943 (CCC Certification)  |
| Europe/CE Mark                    | EN60950 (Complies with 93/68/EEC)                                 |
| Germany                           | S License   |
| International                     | IEC60950 (CB Report and Certificate)                              |
| Nordic Countries                  | EMKO-TSE (74-SEC) 207/94  |
| Russia                            | GOST 50377-92   |
| United States                     | UL60950 – CSA 60950 (UL and cUL)                                  |
| <b>Electromagnetic Capability</b> |   |
| Australia, New Zealand            | AS/NZS 3548 (Based on CISPR 22)                                   |
| Canada                            | ICES-003  |
| China                             | GB9254 & 17625 (CCC Certification)                                |
| Europe/CE Mark                    | EN55022, EN55024 & EN61000-3-2/-3-3<br>(complies with 89/336/EEC) |
| International                     | CISPR 22  |
| Japan                             | VCCI  |
| Korea                             | RRL, MIC 1997-41 & 1997-42  |
| Russia                            | GOST 29216-91 and 50628-95  |
| Taiwan                            | CNS13438  |
| United States                     | FCC, Part 15  |