



HARDWARE SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Configuration	19-inch rack mount, 4RU height
Dimensions (actual)	6.9" H X 16.9" W X 26" D, 17.5cm H X 43cm W X 66cm D
Dimensions (in shipping carton)	18"H X 24"W X 36"D, 46cm H X 61cm W X 92cm D
Weight (actual)	92 lbs, 42 kgs
Weight (in shipping carton)	105 lbs, 47 kgs
Power Supply	110-240 VAC, 50-60 Hz, 8.0 A @ 115 VAC, 4 A @ 220 VAC 2+1 Redundant - hot swappable to total 3 power supplies

Rear Panel

Traffic Ports (1GbE model)	Four 1GbE SFP ports (Available with any combination of Copper or Fiber SFP modules)
Traffic Ports (10GbE model)	Two 10GbE XFP ports (Standard two SR XFP modules with LC connectors) (Optional LR available)
Management Port	RJ45 Gigabit Ethernet (copper)
Serial Port	DB-9M
SVGA video port	DB15

Front Panel

Power switch, power and hard drive status LEDs

Environmental Requirements (Operating)

Temperature	+10 C to +35 C
System Cooling Requirements	.3360 BTU/hour

Environmental Requirements (Non-operating)

Temperature	-40 C to +70 C
Humidity	.90% @ 28 C, non-condensing

REGULATORY CONFORMITY

Safety/EMC Class A

Canada	UL60950 – CSA 60950
Europe/CE Mark	EN60950
International	IEC60950 (CB Report and Certificate)
United States	UL60950 – CSA 60950 (UL and cUL)

Electromagnetic Capability - Class A

Australia	AS 3548
Canada	FCC, Part 15
Europe/CE Mark	EN55022, EN55024
India	EMC testing
Japan	VCCI
Korea	RRL, MIC
Taiwan	BSMI Report
United States	FCC, Part 15